



O2 Sensor Bung & Plug Kits

Available in both Mild Steel & Stainless Steel



**PERFECT FOR
HIGH PERFORMANCE,
CUSTOM & REPAIR JOBS!**

Walker's bung kits feature 6 popular bungs and include plugs, gaskets and flanges. These handy kits will save busy technician's time and increase profits.

Bungs & Plugs also available in bulk quantities!

Custom Bung & Plug Kits available!

**CALL US FOR MORE
INFORMATION!**



Steel Bungs, Plugs
and Flanges WPA-105

Stainless Steel Bungs,
Plugs and Flanges
WPA-105SS



What is included:

WPA-105SS - Stainless Steel

Part Number	Qty	Description	Re-Fill No.	Qty
85-417	2 Ea	Flange, 38-44mm	85-417	1 Ea.
85-418	2 Ea	Flange, 44-54mm	85-418	1 Ea.
90-164SS	5 Ea	Stainless Steel Bung 18mm	90-164SSP	5 Ea.
90-184SS	5 Ea	Stainless Steel Bung 18mm (Stepped)	90-184SSP	5 Ea.
90-185SS	5 Ea	Stainless Steel Bung 18mm (Plug)	90-185SSP	5 Ea.
90-186SS	5 Ea	Stainless Steel Bung 10mm (Stepped)	90-186SSP	5 Ea.
90-187SS	5 Ea	Stainless Steel Bung 12mm (Stepped)	90-187SSP	5 Ea.
90-190SS	5 Ea	Stainless Steel Bung 18mm (Angled)	90-190SSP	5 Ea.
90-195SS	5 Ea	Stainless Steel Bung 18mm (1")	90-195SSP	5 Ea.
165-197	2 Ea	Gasket, 44-54mm Flange	165-197	1 Ea.
165-202	2 Ea	Gasket, 38-44mm Flange	165-202	1 Ea.

WPA-105 - Steel

Part Number	Qty	Description	Re-Fill No.	Qty
85-417	2 Ea	Flange, 38-44mm	85-417	1 Ea.
85-418	2 Ea	Flange, 44-54mm	85-418	1 Ea.
90-164	5 Ea	Steel Bung 18mm	90-164P	5 Ea.
90-184	5 Ea	Steel Bung 18mm (Stepped)	90-184P	5 Ea.
90-185	5 Ea	Steel Bung 18mm (Plug)	90-185P	5 Ea.
90-186	5 Ea	Steel Bung 10mm (Stepped)	90-186P	5 Ea.
90-187	5 Ea	Steel Bung 12mm (Stepped)	90-187P	5 Ea.
90-190	5 Ea	Steel Bung 18mm (Angled)	90-190P	5 Ea.
90-195	5 Ea	Steel Bung 18mm (1")	90-195P	5 Ea.
165-197	2 Ea	Gasket, 44-54mm Flange	165-197	1 Ea.
165-202	2 Ea	Gasket, 38-44mm Flange	165-202	1 Ea.

WALKER PRODUCTS INC. • 525 West Congress Street, Pacific, MO 63069

Customer Service: 1 (636) 257-1700 • Office: 1 (636) 257-2400 • Fax: 1 (636) 257-6211

Technical Support: 1 (844) 252-0114 • www.walkerproducts.com

YOUR FIRST CHOICE IN QUALITY PRODUCTS



Walker
walkerproducts.com

O2 Sensor Bungs, Plugs, Flanges and Gaskets



90-164*

O2 Sensor Bung
1215 Mild Steel
18mm Threads
1.0" OD x 0.400" Thick



90-164SS*

O2 Sensor Bung
303 Stainless Steel
18mm Threads
1.0" OD x 0.400" Thick



90-164SS-C

O2 Sensor Bung w/ Curve
303 Stainless Steel
18mm Threads
1.0" OD x 0.400" Thick



90-184*

O2 Sensor Bung - Stepped
1215 Mild Steel
18mm Threads
1.0" OD x 0.875" Step x 0.530" Thick



90-184SS*

O2 Sensor Bung - Stepped
303 Stainless Steel
18mm Threads
1.0" OD x 0.875" Step x 0.530" Thick



90-184SS-M

O2 Sensor Bung - Stepped
316 Stainless Steel
18mm Threads
1.0" OD x 0.875" Step x 0.530" Thick



90-186*

O2 Sensor Bung - Stepped
1215 Mild Steel
10mm Threads
0.980" OD x 0.735" Step x 0.320" Thick



90-186SS*

O2 Sensor Bung - Stepped
303 Stainless Steel
10mm Threads
0.980" OD x 0.735" Step x 0.320" Thick



90-187*

O2 Sensor Bung - Stepped
1215 Mild Steel
12mm Threads
0.985" OD x 0.740" Step x 0.315" Thick



90-187SS*

O2 Sensor Bung - Stepped
303 Stainless Steel
12mm Threads
0.985" OD x 0.740" Step x 0.315" Thick



90-189*

O2 Sensor Bung
1215 Mild Steel
12mm Threads
1.0" OD x 0.500" Thick



90-189SS*

O2 Sensor Bung
303 Stainless Steel
12mm Threads
1.0" OD x 0.500" Thick



90-190*

O2 Sensor Bung - 62° Angle
1215 Mild Steel
18mm Threads
1.0" OD x 0.975" Thick



90-190SS*

O2 Sensor Bung - 62° Angle
303 Stainless Steel
18mm Threads
1.0" OD x 0.975" Thick




90-195*

O2 Sensor Bung
1215 Mild Steel
18mm Threads
1.0" OD x 1.000" Thick



90-195SS*

O2 Sensor Bung
303 Stainless Steel
18mm Threads
1.0" OD x 1.000" Thick



90-195SS-C

O2 Sensor Bung w/ Curve
303 Stainless Steel
18mm Threads
1.0" OD x 1.000" Thick



90-199*

O2 Sensor Bung
1215 Mild Steel
18mm Threads
1.0" OD x 0.500" Thick



90-199SS*

O2 Sensor Bung
303 Stainless Steel
18mm Threads
1.0" OD x 0.500" Thick



90-206SS-C

O2 Sensor Bung - 62° Angle w/ Curve
303 Stainless Steel
18mm Threads
0.985" OD x 0.824" Thick



90-207SS-C

O2 Sensor Bung w/ Curve
303 Stainless Steel
18mm Threads
0.985" OD x 0.550" Thick



90-208SS

O2 Sensor Bung w/ Curve
304L Stainless Steel
18mm Threads
1.0" OD x 0.434" Thick



90-211

O2 Sensor Bung
1215 Mild Steel
18mm Threads
1.0" OD x .375" Thick



90-213-C

O2 Sensor Bung - 60° Angle w/ Curve
1215 Mild Steel
18mm Threads
1.0" OD x 1.025" Thick



90-214SS

O2 Sensor Bung
303 Stainless Steel
1/8-27 NPT Threads
0.500" OD x 0.500" Thick



90-185*

O2 Sensor Bung Plug
1215 Mild Steel
18mm Threads
1.0" Hex 0.650" Thick
Use with 1401FP Copper Washer



90-185SS*

O2 Sensor Bung Plug
303 Stainless Steel
18mm Threads
1.0" Hex 0.650" Thick
Use with 1401FP Copper Washer



90-200*

Bung Plug - Internal 8mm Hex
1215 Mild Steel
18mm Threads
0.875" OD x 0.510" Thick
Use with 1401FP Copper Washer



90-200SS*

Bung Plug - Internal 8mm Hex
303 Stainless Steel
18mm Threads
0.875" OD x 0.510" Thick
Use with 1401FP Copper Washer



90-203*

Bung Plug - Internal 6mm Hex
1215 Mild Steel
12mm Threads
0.625" OD x 0.400" Thick
Use with 215FP Copper Washer



90-203SS*

Bung Plug - Internal 6mm Hex
303 Stainless Steel
12mm Threads
0.625" OD x 0.400" Thick
Use with 215FP Copper Washer



90-204*

O2 Sensor Bung
1215 Mild Steel
12mm Threads
0.625" Hex 0.570" Thick
Use with 215FP Copper Washer



90-204SS*

O2 Sensor Bung
303 Stainless Steel
12mm Threads
0.625" Hex 0.570" Thick
Use with 215FP Copper Washer



90-210

Plug - 12mm Internal Threads
1215 Mild Steel
18mm Threads
0.875" Hex 0.368" Thick
Use with 1401FP Copper Washer



90-210SS

Plug - 12mm Internal Threads
303 Stainless Steel
18mm Threads
0.875" Hex 0.368" Thick
Use with 1401FP Copper Washer



90-212

Plug - 1/8-27NPT Internal Threads
1215 Steel, Zinc Plated
18mm Threads
1.0" Hex 0.65" Thick
Use with 1401FP Copper Washer



85-417

O2 Sensor Flange
38mm x 44mm
18mm Threads



85-418

O2 Sensor Flange
44mm x 54mm
18mm Threads



85-419

O2 Sensor Boss
1215 Mild Steel, 18mm Threads
0.460" Thick, M8 x 1.25" Studs



165-197

O2 Sensor Flange Gasket
44mm x 54mm



165-202

O2 Sensor Flange Gasket
38mm x 44mm



215FP

Copper Seal Washer
Pack of 10 pieces
I.D. 0.470" x O.D. 0.625" x 0.030 Thick



1401FP

Copper Seal Washer
Pack of 10 pieces
I.D. 0.710" x O.D. 0.910 x 0.045 Thick

**Note: All part numbers followed with * on this page are available in a box of five pieces.
The part number for a box of five will have a "P" suffix. Example: 90-186P or 90-187SSP**

© Walker Products Inc. 2017



Walker
walkerproducts.com

O2 Sensor Tools

88-823

O2 Sensor Socket

Standard O2 Sensors
6 Point With 25/32" Wire Opening
Fits 7/8" or 22mm 3/8" Drive



88-830

O2 Sensor Wrench

12 & 6 Point 2 1/8" Offset



Includes a 12 point and 6 point socket giving the technician the ultimate tool to remove O2 Sensors in confined areas.

The 12 point side enables the technician twice the number of clock angle attachment positions. This gives the technician the maximum accessibility to remove O2 Sensors in difficult areas.

The 6 point side provides the technician the maximum holding power for O2 Sensors that are corroded in place.

The new beefy design is 25% stronger.

Fits with all configurations of O2 Sensor wire/connectors.

Designed with additional offset enabling use on LTI Gen II 5.7L HO MPFI V-8 found in the 1992 and later Chevrolet Corvette, 1993 and later Camaro and 1993 and later Pontiac Firebird / Trans Am also 1989 and later Corvette ZR1 with the LT5 5.7L DOHC SFI V-8

88-829

O2 Sensor Wrench

12 & 6 Point



Includes a 12 point and 6 point socket giving the technician the ultimate tool to remove O2 Sensors in confined areas.

The 12 point side enables the technician twice the number of clock angle attachment positions. This gives the technician the maximum accessibility to remove O2 Sensors in difficult areas.

The 6 point side provides the technician the maximum holding power for O2 Sensors that are corroded in place.

The new beefy design is 25% stronger.

Fits with all configurations of O2 Sensor wire/connectors.

88-831

O2 Sensor Wrench

Shielded Applications



This unique tool has been designed to R&R shielded O2 Sensors currently found on Toyota and Lexus vehicles.

The depth and outer diameter of the socket are critical features enabling it to fit in the limited space of the heat shield.

This tool features a 12 point double hex enabling the technician twice the number of clock angle attachment positions versus a 6 point design. For maximum strength this tool is forged chromoly steel and comes in a black finish.



Walker
walkerproducts.com

O2 Sensor Tools

88-832

O2 Sensor Bung Thread Repair Kits

Includes: 1 Tap, 1 Insert Tool, 6 Repair Inserts



88-835

O2 Sensor Wrench

6 Point 3/8" Drive
1.2" Overall Depth



The 6 point side provides the technician the maximum holding power for O2 Sensors that are corroded in place.

Fits with all configurations of O2 Sensor wire connectors.

88-836

O2 Sensor Socket


Standard O2 Sensors
6 Point With 9/32" Wire Opening
Fits 7/8" or 22mm 3/8" Drive



88-833

O2 Sensor Bung Insert Kit

Includes: 6- Repair Inserts



88-834

O2 Sensor Wrench

Standard O2 Sensors
Fits 7/8" or 22mm 2" Overall Depth



88-837

O2 Sensor Chaser

M18x1.5 Thread Chaser 3/8" Drive

